

Cemimax A600

LINOLEUM ADHESIVE

Water-based dispersion adhesive for linoleum floor coverings on absorbent substrates. Wet adhesives with a short drying time. For interior use.

ESPECIALLY SUITABLE FOR

Linoleum floor coverings in sheets and panels In residential and commercial areas

PRODUCT PROPERTIES

- Very high initial tack and final bonding strength
- Bonding layer has durable resilience
- Low drying time
- Solvent free

BINDERS

Modified polyacrylate-copolymers with bond strengthening resins.

TECHNICAL DATA

Under normal conditions at 20°C

Packaging: 15kg Plastic drum

Shelf-life: Min. 12 months

Colour: Cream-white

Working temperature: Min. 15 °C at floor level

Consumption: 400g/m²

Drying time: 30 minutes

Set to traffic: After 24hours

Final strength: After 3 days

Open time: 5-30mins

APPLICATION

- Allow primers and smoothing compounds to dry thoroughly. Refer to the product Data Sheet for the products used.
- Stir thoroughly the product before use, Apply it evenly on the surface of substrate by using B1 toothed trowel. After short open time of 20-40 min. the substrate is ready to accept above flooring material.
- Lay the covering on the full surface. rolling with 50kg roll over the covering to ensure removal of residual air. Make sure that the adhesive has transferred to the back of the flooring material.
- The adhesive will be dried after 24h, and set to foot traffic after 48h.

NOTES

The product should be protected against frost and direct light during transportation, storage and application. Application temperature should not be lower than 5°C

DISPOSAL

Dispose of empty packaging according to local regulations.

