



# Cemimax PP3

## FEATHER EDGE SMOOTHING COMPOUND

### 1. Identification of the product and company

#### 1.1 Product name

Cemimax A350 Waterborne resilient adhesive

#### 1.2 Manufacturer

SHANGHAI NATURE BUILDING MATERIALS CO.,LTD

NO.4 th.floor,The 9 th Buildong Kangjian Plaza.NO.1228 Zhennan road,Putuo district,Shanghai PRC. TEL:86-21-64859010 FAX:86-21-64859020

### 2. Composition/information on ingredients

Cement smoothing compound based on special cements, calicium sulphate, quartz sand and chalk.

Hazardous Substances	CAS NO	EINECS NO	% SHARE	Classification
Cement	659997-15-1		10-25	XI R 38,41

### 3. Hazards identification

The cement content in this product makes the following labeling required: X Irritant Contains cement

Special hazard instructions:

R38 Irritating to skin

R41 Risk of serious damage to eyes

Additional information: Low in Chromate(<2 ppm) acc. Directive 2003/52/EC

Very low emission ,EMICODE EC 1.

### 4. First-aid measures

After skin contact: Wash with water and soap.

After contact with eyes: Rinse thoroughly with water and consult a doctor.

After swallowing: Do not induce vomiting, medical help is necessary, show this label/safety data sheet.

### 5. Fire-fighting measures

No special measures required. Extinguishing agents should be appropriate for the location.

### 6. Accidental release measures

Mechanically remove the spilled material, soak up any residue (e.g. with sand or saw-dust) and dispose according to local and national disposal regulations. Do not allow to disperse into water systems.

### 7. Handling and storage

#### 7.1 Handling

Avoid producing dust as well as contact with eyes and skin. When mixing wear a protective dust-mask. At breaks and end of work, wash hand and apply shin cream.

#### 7.2 Storage

Protect from water and moisture.

### 8. Exposure limits / personal protection

#### 8.1 Exposure limits

Ingredients with limit values that require monitoring at the workplace:

Hazardous Substances	CAS NO	% SHARE	OEL(mg/m3)
Quartz	14808-60-7	25-50	0.15
Cement	65997-15-1	10-25	5

#### 8.2 Personal protection

Avoid contact with eyes and skin. When mixing wear a protective dust-mask.

Protection of hands; Use nitrile impregnated cotton-gloves.

In case of splashes or formation of dust wear safety goggles.





# Cemimax PP3

## FEATHER EDGE SMOOTHING COMPOUND

At breaks and end of work, wash hand and apply skin cream.

### 9. Physical and chemical properties

Form: Powder

Colour: grey

Odour: of cement

Density (20°C): app. 1100kg/m<sup>3</sup>

Solubility in water (20°C): Sets hydraulically with water

Flash point: not applicable

Ignition temperature: not applicable

Explosion limits: no risk of explosion

pH-value: app. 12

### 10. Stability and reactivity

When used as stated, produces no thermal decomposition, no hazardous products of decomposition and no hazardous reactions.

### 11. Toxicological information

The product reacts with water and moisture to produce strong alkaline and long exposure can, therefore, lead to irritation of the skin.

Primary irritant effect:

On the skin :Irritant to skin and mucous membranes.

On the eye: Strong irritant with the danger of severe eye injury.

Sensitization: Low in chromate, therefore no sensitizing effects known.

The cured, Solidified product is non-irritant.

### 12. Ecological information

Do not allow the product to disperse into drains, sewers or ground.

### 13. Disposal considerations

Where possible, collect product residues and re-use. Do not allow to get into drains, sewers or ground. Empty, dust-free paper packaging is recyclable. Collect waste product, mix with water, allow to harden and dispose as construction waste.

### 14. Transport information

Not hazardous goods according to transport regulations: Road Transport , Sea Transport , Air Transport .

### 15. Regulatory Information

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

### 16. Other Information

Recommended use: Raw material, for industrial use only

Any other intended applications should be discussed with the manufacturer.

