



Safety Data Sheet

Product Name: **ARCHITECTURAL GROUT** CAS # **14808-60-7 - Quartz (respirable fraction)**

Recommended use of the chemical and restriction on use: Ceramic tile grout construction product

Supplier: Morgan Ceramic Tile Adhesives 24 Hanwell Way Bassendean WA 6054

Telephone 08 9279 8911

Facsimile 08 6278 1152

EMERGENCY TELEPHONE NUMBER

08 9279 8911 (during business hours)

Email chemist@morganadhesives.com.au

Website www.morganadhesives.com.au

SECTION 2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture

Skin corrosion/irritation – category 2

Serious eye damage – category 1

Skin sensitizer – category 1

Specific target organ toxicity (single exposure) – category 3

Signal Word - DANGER

**Hazard Statements**

H315: Causes skin irritation

H317: May cause an allergic skin reaction

H318: Causes serious eye damage

H335: May cause respiratory irritation

Precautionary Statements

P261: Avoid breathing dust

P271: Mix only outdoors or in a well ventilated area

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of soap and water

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

P310: Immediately call a POISON CENTRE or doctor/physician

P312: Call a POISON CENTRE or doctor/physician if you feel unwell

P333+P313: If skin irritation or rash occurs: Get medical attention

P362: Take off contaminated clothing and wash before reuse

P403+P223: Store in a well ventilated place. Keep container tightly closed

P405: Store locked up

P501: Dispose of contents/container in accordance with local regulations

HAZARDOUS CHEMICAL. NON DANGEROUS GOODS. NOT A SCHEDULED POISON

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Chemical	Cas#	%w/w
Quartz (respirable fraction)	14808-60-7	< 1
Cement	65997-15-1	10 - < 30
NON HAZARDOUS Chemicals		to 100

SECTION 4 – FIRST AID MEASURES

Ingestion: Do not induce vomiting. Rinse the mouth with water. Give fruit juice or water to drink. Seek immediate medical assistance.

Eye Contact: Hold the eyelids open and irrigate the eyes with copious amounts of water for at least fifteen minutes. Seek immediate medical assistance.

Skin Contact: Remove the contaminated clothing. Rinse the exposed areas thoroughly with water. Clean the contaminated clothing before re-using.

Inhaled: Move the person to a source of fresh air. Seek medical advice if symptoms such as coughing persist.

SECTION 5 – FIRE FIGHTING MEASURES

HAZCHEM CODE: NONE ALLOCATED

This product is not combustible. Decomposition of this product will result in the generation of toxic oxides of carbon. Flames on or in the vicinity of this product can be extinguished using conventional fire fighting agents and procedures.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Avoid dust formation. For large spills, wear PVC gloves, dust goggles, overalls and a disposable Class P1 respirator (AS1715-1991). Do not allow the product to enter drains or surface water. Remove dry using conventional tools.

SECTION 7 – HANDLING AND STORAGE

Store cool and dry. During storage and transport keep the product away from water based products and corrosive substances.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Standards: An exposure standard for this product has not been allocated. The use of this product can lead to the generation of respirable dust. Morgan therefore advises that the time weighted average (TWA) airborne concentration of the product should not exceed 0.1mg per cubic metre of contaminated air.

Engineering Controls: Morgan advises that the product should be carefully mixed into the recommended volume of water in a large bucket and in a well ventilated area so as to minimise the tiler's exposure to respirable dust.

Personal Protective Equipment: Always handle and use this product with common sense and good industrial hygiene practices. Tilers should avoid all unnecessary skin contact with this product. Chronic health effects can be avoided by the use of a barrier cream.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Powder of various colours	Solubility:	Slightly soluble
Odour:	Similar to cement	Specific gravity:	> 1
Vapour Pressure:	Not relevant	Vapour Density:	Not relevant
Melting Point:	>1200 degrees Celsius	Boiling Point:	Not available
Flammability:	Not combustible	Explosion Limits:	Not relevant
pH:	12 (1% solution)	Ignition Temperature:	Not relevant

SECTION 10 – STABILITY AND REACTIVITY

Chemical stability:	Stable when stored in a dry and cool environment.
Conditions to avoid:	Moist and warm storage environment.
Incompatible materials:	Avoid exposing product to acids.
Hazardous decomposition products:	Product will release oxides of carbon.
Hazardous reactions:	Product will react with acids.

SECTION 16 – OTHER INFORMATION

The information contained herein is considered to be accurate and up to date. However, no warranty is expressed or implied regarding the accuracy of the information contained herein or the results to be obtained from the use thereof. Morgan Ceramic Tile Adhesives will not assume responsibility for the personal injury or for the damage caused to the property of vendees, users or third parties from the storage or use of this product. Vendees or users assume all risk associated with the use of this product.