

Cemimax DP60

PRIMER

Low emission, multi-purpose dispersion primer for existing surfaces

DESCRIPTION

Dispersion primer with a wide range of applications, for interior use only.

ESPECIALLY SUITABLE FOR

Use on surfaces with well-bonded, waterproof adhesive and smoothing compound residues.

PRODUCT PROPERTIES

- Ready to use.
- Excellent bond
- Rapid drying
- High coverage
- Solvent-free.

BINDERS

Modified styrene-acrylate copolymers, wetting and anti-foaming-agents, preservatives and water.

TECHNICAL DATA

Under normal conditions at 20°C

Packaging: Plastic bucket

Packsize: 20 kg & 5 kg

Shelf-life: 12 months

Application Temp Range: +5°C - 35°C

Consumption: Approx. 12m² /1 Litre

Drying time: 4-6hours

Touch Dry: 15-20mins

APPLICATION

- Thoroughly stir container for until all settled clumps are off of the bottom and suspended in the liquid.
- The surface should be clean, dry, and free of any loose particles, dust or any granulates. The substrate should be cleaned thoroughly
- The product can be diluted with water. The water proportion base on the substrate situation. (note: if the existing substrate is ceramic tile, it shall not be diluted)
- Apply the primer evenly to fully cover the surface using a fine-pored foam roller.
- Drying times: allow to dry to a clear, transparent, almost tack-free film. Dependant upon floor temperature and humidity. In favourable climatic conditions and on absorbent surfaces, a drying time of 1-3 hours is normally adequate.
- Clean equipment immediately with water. Mineral spirits may be used to remove primer that has dried on tools.

SUBSTRATE PREPARATION

The subfloor should be thoroughly cleaned, dry, free of debris, and no loosely bonded surfaces. Make sure there are no active cracks, completely free of contaminants like curing compounds, solvent based markers or paint, oil, grease, and wax that would block absorption into the substrate. Test substrate in accordance with applicable standards relative to moisture content. Any weakly bonded material such as adhesive residue, leveling compounds, floor coverings or coatings must be removed by shot blasting, abrading, grinding, or scraping. Do not apply over water-soluble adhesive. If applying over an MVR it must be properly installed following the installation instructions.

NOTES

The product should be protected against frost and direct light during transportation, storage and application. Application temperature should not be lower than 5°C.

DISPOSAL

Dispose of empty packaging according to local regulations.

